




## HASSLE-FREE DISINFECTION

Heat exchangers surface disinfection is the bottom line of AHU's disinfection, UV STICK AX-SCR system make it easy with an **on-coil mounting kit** and the easy power up of multiple devices through 1 single power supply cable.


The goal is to **continuously target bacteria, viruses, mold and biofilms that proliferate on Coils, air filters, duct walls and drain pans**, preventing them from becoming reservoirs for pathogen growth.

**“-AX” Model** is made in Aluminum, with a mirror bright plain reflector.



## KEY PRODUCT FEATURES

- **Made for the Task**, these single-lamp modules are specific for Coils treatment. They avoids settling and proliferation of Biofilm on the surfaces.
- **One for All**, these single-lamp modules can fit easily in many different environments and include integrated power supplies. Connect and disinfect.
- **Increased Disinfection Performance**, with High-Output UV-C lamps (253,7 nm) and internal mirror bright aluminum reflector.
- **Built to last**, with high-quality material tested to resist UV.
- **Protected**, IP55 Rated with UVLON™ available to avoid glass falling and protect against temperature fluctuations.
- **Combine and Connect**, -SCR models, to connect multiple devices and create your customized disinfection solution, all powered through a single cable.
- **Choose your installation layout**, different mounting kits available, to adapt to all sizes and different kind of surface/coil treatment.



Healthcare sector  
(hospitals - clinics)



HVAC -  
Air conditioning systems



Food and pharmaceutical  
production industry



Ho.Re.Ca.



Schools -  
Offices - Shops



Large environments



Gyms -  
Wellness centres



Transport

# TECHNICAL TABLE

	UV-STICK-AX-SCR				
	UVSTCK40HAXSCR	UVSTCK60HAXSCR	UVSTCK90HAXSCR	UVSTCK120HAXSCR	UVSTCK150AXSCR
LAMP LIFE (hours)*	≤ 18.000				
REPLACEMENT LAMP	n°1 CHS-40WHF	n°1 CHS-60WH	n°1 CHS-90WHF	CHS-120WH	CHS-75W
TOTAL CONSUMPTION (W)	40	60	90	120	76
DIMENSIONS l x p x h	496 x 58 x 92 mm (20 x 2 x 4 in)	659 x 58 x 92 mm (26 x 2 x 4 in)	953 x 58 x 92 mm (38 x 2 x 4 in)	1233 x 58 x 92 mm (49 x 2 x 4 in)	1613 x 58 x 92 mm (64 x 2 x 4 in)
WEIGHT	1 Kg (2 Lb)	1,1 Kg (2 Lb)	1,2 Kg (3 Lb)	1,4 Kg (3 Lb)	1,6 Kg (4 Lb)
TREATED SURFACE	0,25 ÷ 0,50 m <sup>2</sup> (3÷ 5 ft <sup>2</sup> )	0,35 ÷ 0,70 m <sup>2</sup> (4÷ 8 ft <sup>2</sup> )	0,50 ÷ 1,00 m <sup>2</sup> (5÷ 11 ft <sup>2</sup> )	0,65 ÷ 1,30 m <sup>2</sup> (7÷ 14 ft <sup>2</sup> )	0,85 ÷ 1,70 m <sup>2</sup> (9 ÷ 18 ft <sup>2</sup> )
PROTECTION RATING	IP 55				
POWER SUPPLY	On-board power supply always included.				
ELECTRICAL CONNECTION	Electric power supply cable 3x1 mm <sup>2</sup> of 1,2 m. with socket/plug system (ICC) quick connection (IP55) + output cable of 0,5 m. (with flying plug) to connect the next device (serial connection in parallel).				

\* continuous operation

## TROUBLE-FREE INTEGRATION AND INSTALLATION



- We provide the optimal point of integration for every product without requiring changes to your system.
- Mounting and powering the device can be done without complex requirements.
- Ongoing maintenance only takes a few minutes to replace lamps when necessary.

## SOFTWARE ENGINEERED DISINFECTION

From our in-depth know-how on the subject and with our proprietary dosage calculation software we can simulate device performance and validate effectiveness in every application.

Calculation Software




## TECHNICAL DRAWINGS

Every Light Progress Product is available in detailed DWG and STEP files for your design-in and specification clarity.

VIEW or DOWNLOAD now



## MICROBIAL TESTS AND EFFICACY



**Up-to log3 microbial reduction on Airflow, Coils and HVAC surfaces, 24 hours a day.**

Light Progress customers rely on our extensive history of third party testing and proven efficacy to meet any level of disinfection validated against literally any virus or microorganism.

We understand your need to meet Regulatory Requirements and Industrial Standards as we help you achieve microbial load reduction using our UV systems.

**Light Progress Group SRL**  
Anghiari (AR) ITALIA  
P: (+39) 0575 749255  
E: info@lightprogress.it  
W: www.lightprogress.it

**Light Progress GmbH**  
Aschaffenburg DEUTSCHLAND  
P: (+49) 6021-8663700  
E: info@lightprogress.it  
W: www.lightprogress.de

**Light Progress LLC**  
Austin, TX USA  
P: (+1) 833-882-4255  
E: americas@lightprogress.it  
W: www.lightprogress.us

**OFFICIALLY DISTRIBUTED BY:**