
PRODUCT SPECSHEET



SIZED TO INSTANT DISINFECTION


A grid of UVC lamps is the key to **treat the entire air flow and enhance filter performances**, UV DUCT-SQ is the perfect device to achieve a total and uniform air disinfection.

UV-DUCT-SQ has been designed to adapt to different sizes and ducts sections, placing one device to cover the surface or matching more devices together side-by-side, one on the other (overlapping), in series, etc. using scroll-in "U"profile, like filters or its original **mounting kit with adjustable sizes**.



KEY PRODUCT FEATURES

- -> Built to perform in any condition, its compact form factor fits in the space of a filter.
- → Equally spaced lamps, to treat homogeneously the airflow, when the duct section is covered.
- → Increased Disinfection Performance, with High-Output UV-C lamps (253,7 nm).
- → Built to Last, in high-quality Stainless Steel AISI 304, all material tested for UV resistance.
- -> Protected, resistant to dust and splashes with an IP55 Rating.
- → Integrate and Monitor, your operation with visual lamp failure alarm signals, hour counter, and lamp replacement alert.



















Healthcare sector

Food and pharmaceutic

Ho.Re.Ca.

Schools -

Large envir

vironments

TECHNICAL TABLE

	UV-DUCT-SQ					
	UVDCTSQ 4/40HCS	UVDCTSQ 4/90HCS	UVDCTSQ 4/120HCS	UVDCTSQ 6/40HCS	UVDCTSQ 6/90HCS	UVDCTSQ 6/120HCS
LAMP LIFE (hours)*	≤ 18.000					
REPLACEMENT LAMP	N° 4 CHS-40WH	N° 4 CHS-90WH	N° 4 CHS-120WH	N° 6 CHS-40WH	N° 6 CHS-90WH	N° 6 CHS-120WH
LAMP POWER (W)	40x4 = 160	90x4 = 360	120x4 = 480	40x6 = 240	90x6 = 540	120x6 = 720
DIMENSIONS lxpxh	90 x 450 x 496 mm (4 x 18 x 20 in)	90 x 450 x 953 mm (4 x 18 x 38 in)	90 x 450 x 1234 mm (4 x 18 x 49 in)	90 x 600 x 496 mm (4 x 24 x 20 in)	90 x 600 x 953 mm (4 x 24 x 38 in)	90 x 600 x 1234mm (4 x 24 x 49 in)
WEIGHT	5 Kg 11 Lb	5,50 Kg 12 Lb	6 Kg 13 Lb	6 Kg 13 Lb	6,50 Kg 14 Lb	7,00 Kg 15 Lb
PROTECTION RATING	IP 55					
POWER SUPPLY	Supply Box (with power supply, with access security, hour counter, UV lamp fault control and LED synoptic) to be purchased separately. Optional Control Board for the management of multiple lamps (with access security, hour counter, UV lamp fault control and LED synoptic).					
SUPPLY BOX DIMENSIONS	314 x 410 x 128 mm (12 x 16 x 5 in)					
ELECTRICAL CONNECTION	Power Supply Cable to be purchased separately (3 m or 10 m), IP67					

* continuous operation

TROUBLE-FREE INTEGRATION AND INSTALLATION



- We provide the optimal point of integration for every product without requiring changes to your system.
- Mounting and powering the device can be done without complex requirements.
- Ongoing maintanance only takes a few minutes to replace lamps when necessary.


SOFTWARE ENGINEERED DISINFECTION

From our in-depth know-how on the subject and with our proprietary dosage calculation software we can simulate device performance and validate effectiveness in every application.

TECHNICAL DRAWINGS

Every Light Progress Product is available in detailed DWG and STEP files for your design-in and specification clarity.

MICROBIAL TESTS AND EFFICACY



Light Progress Group SRL Anghiari (AR) ITALIA P: (+39) 0575 749255 E: info@lightprogress.it W: www.lightprogress.it

Light Progress GmbH Aschaffenburg DEUTSCHLAND P: (+49) 6021-8663700 E: info@lightprogress.it W: www.lightprogress.de



Escherichia Coli

- Bacillus Subtilis

Pseudomonas Aeruginosa Salmonella Typhimurium

- Listeria Monocytogenes

Staphylococcus Aureus

- Aspergillus Niger

Light Progress LLC Austin, TX USA P: (+1) 833-882-4255 E: americas@lightprogress.it W: www.lightprogress.us

Calculation Software





Light Progress customers rely on our extensive history of third party testing and proven efficacy to meet any level of disinfection validated against literally any virus or microorganism.

We understand your need to meet Regulatory Requirements and Industrial Standards (such as VDMA) as we help you achieve microbial load reduction using our UV systems.

OFFICIALLY DISTRIBUTED BY: