## **UV - STYLO - NX** compact UV-C system

UV-STYLO-NX can be installed in places where space is very limited, for example for the disinfection of packaging film, conveyors, bottling lines for disinfection of bottles and their closing capsules, as well as the treatment of the same food products, for decontamination from germs of any surfaces i.e. conveyor belts, products, packaging, etc.

UV-STYLO-NX is designed specifically for applications in the food industry, and that is why one of its features is also the IP67 protection level, allowing it to combine perfectly with damp environments and water splashes.

Traditional cleaning methods are, often, not sufficient to ensure high levels of hygiene, which can be achieved only by the use of UV-C technology.

As a matter of fact, food processes have the need to be controlled, by monitoring hygiene levels, to keep very high quality standards.

It is shown how, in the food industry, an increased in hygiene level allows a consequent and general of product quality improvement and, more specifically, UV-STYLO-NX achieves the eliminantion (99%) of bacteria such as *Bacillus*, *Coli*, *Clostridium*, *Legionella*, *Vibrio*, *Salmonella*, *Pseudomonas*, *Staphylococcus*, etc. in just 4 minutes of operation.

High disinfection levels of UV-STYLO can be otherwise achieved but only with the use of chemicals, hazardous to health and harmful to the environment, as well as costly.



## WHAT ARE UV-C RAYS?

Light in a broad sense can be divided in visible, infra-red and ultraviolet rays.

Ultra-violet rays (invisible) can be classified in:

- UV A (with tanning properties)
- UV B (with therapeutic properties)
- UV C (with germicidal properties)

The germicidal effects of the UV-C radiation destroy DNA of Bacteria, Viruses, Spores, Fungi, Moulds and Mites avoiding their growth and proliferation.

UVGI technology is a physic disinfection method with a great cost/benefits ratio, it's ecological, and, unlike chemicals, it works against every microorganisms without creating any resistance.



Application in industrial machinery



Application scheme



## **TECHNICAL FEATURES**

-UV-C Light Progress selective lamp (emission peak 253.7 nm.) with high output, ozone free, very pure quartz.

- Structure in AISI 304 stainless steel.
- All materials are tested to resist to intense UV-C rays.
- Protection Rating:
  - IP67 (lamp+quartz)
  - IP55 (Cable and supply-box).

- Power supply with electronic ballast specific for Ligh Progress UV-C lamps.

- Supply box (MASTER-STY) or "naked" ballast (-B, Ba) available.
- CE marking (LVD EMC MD RoHS).

## UV - STYLO - NX reduced space requirement, great results



Detail

UV-STYLO-NX consists of a stainless Steel AISI 304 container, with ultra compact dimensions, internally coated with mirror bright aluminium, specific for high UV reflection.

The container houses a UV-C lamp, protected by a pure quartz sleeve (IP67).

Quartz also performs the important function of protecting the UV-C lamp from high and low temperatures, creating an air cushion between the lamp and the external environment, thus increasing UV-C output. A cylinder made of insulating material attached to the steel ase supports the quartz and contains the electrical connection between the lamp and the power cable.

UV-STYLO-NX can be combined with other modules for disinfection in "team" (battery), is available in various lengths and wattages to meet the different use requirements. It is possible to choose between a "naked ballast" or to add a control panel to check operation, alarms and hour-counter separately. (MASTER-STY) (optional).

UV-STYLO-NX is ready to use and does not require any special maintenance, except for the periodical replacement of the lamps. UV-STYLO-NX is entirely manufactured in Italy, with high quality and extremely resistant materials.



**LIGHT** PROGRESS

Loc. San Lorenzo, 40 - 52031 - ANGHIARI (AR) www.lightprogress.com - Tel. +39.0575.74.92.55